LED Area Illumination
Ambiente Area XL

Benefits

- Energy saving up to 70%
- Increases visibility and comfort
- Uses most advanced LED-technology
- High efficient design: up to 101 lm/W luminaire efficacy
- Outdoor ambient resistant -40°C to +60°C
- Integrated die cast aluminium housing ensures good thermal management maximizing life and LED performance
- Protected on against moisture, power dips or surges
- Same model for straight or bended poles, easy finetuning of angle
- Easy to install by one person
- Attractive design
- Built-in smart technology:
  - Luminaire Intelligent Protection System (LIPS)
  - Active Overheat Protection (AOP)
- Mounting height: max. 18 meter

Features

Productgroup	Ambiente
Power supply	Integrated
Input voltage	90 - 305 Vac | 127 - 431 VDC
Frequency	47 - 63 Hz
Input Power (default)	180 Watt
Lumen output (up to)	18208 lm
Efficacy (default)	101 lm/W
Colour temperature (CCT)	3000 | 4000 | 5700 K
Colour rendering index (CRI)	83+ | 73++
Colour consistency	5 Macadam Ellipses
Upward light ratio (ULR)	< 1%
LED-count	50 | 75
Optic	PMMA
Beam optics	Wide area
Housing	Diecast aluminium / tempered safety glass
Mounting	Suits straight and angled poles
Pole diameter	60 - 76 mm
Dimensions	864 x 375 x 178 mm
Adjustable angle	-5° to +10°, bended or straight poles
EOS wireless technology	No
Ingress protection	IP65
Mechanical impact resistance	IK08
Max SCx	0.3 m²
IEC safety class	I
Power factor	0.96 typical
AC harmonics	Less than 10% THD compliant to EN55015
Inrush current	65A 1,2 ms
B-16A fuse	10 pcs
C-16A fuse	14 pcs
Operating temperature	-40°C to +60°C
Rated life (L80B10)	100,000+ hours

AOP Active Overheat Protection

LIPS Luminaire Intelligent Protection System

eos Integrated EOS Technology



RoHS COMPLIANT IP65 EMC CE CB

Bever_Family_Specsheet_02-06-25

Accessories

15354 Ambiente. Pole adapter 76=>60mm. Galvanised steel.

19335 Ambiente XL. Wall bracket. 110mm-Ø76mm arm 0° angle. Steel (galvanized)

Compliances

IEC 60598-1	Luminaires - Part 1: General requirements
IEC 60598-2-3 +A1:2011	Luminaires - Part 2-3: Particular requirements – Luminaires for road and street lighting
IEC 62471:2008	Photobiological safety of lamps and lamp systems
IEC 60068-2-52	Environmental tests - Salt mist
EN 50102	Degree of protection by enclosures for electrical equipment against external mechanical impacts (IK Code)
EN 55015: 2013	Emission - Electrical lighting and similar equipment
EN 61000-3-2: 2006	Limits for harmonic currents emissions
+A1: 2009	
+A2: 2009	
EN 61000-3-3: 2013	Limitation of voltage fluctuations and flicker

All product, product specifications and data are subject to change without notice to improve reliability, function, design or otherwise. Photos and pictures are for illustration purpose only