



Benefits

- + Light fitting protection IP66
- + Minimum ambient temperature up to -40°C
- + Maximum ambient temperature up to 70°C
- + Lifetime: 50,000 hours / L80B10
- + Possibility of using in even higher ambient temperatures under the condition of a shortened service life of the fitting- parameters solved within a particular project
- + Diffuser: translucent polycarbonate (PC) = high mechanical resistance
- + Body: Grey polycarbonate with Al coolers (PC Al) = high mechanical resistance
- + Up to 45% lower electricity consumption when compared to tubes T5
- + Constant luminous flux even in ambient temperature of -40°C
- + Certification: HACCP

Features

Productgroup	Futura
Power supply	Integrated
Input voltage	198 - 264 Vac
Frequency	50 - 60 Hz
Colour temperature (CCT)	4000 Kelvin
Colour rendering index (CRI)	> 80
Housing	PC (high mechanical resistance, UV stability)
Dimensions	1172 x 145 mm
Mounting	Surface mounted
Connection	Terminal block integrated
Ingress protection	IP66
Impact protection	IK10
Ignition temperature	850 °C
IEC safety class	I
Inrush current	45 A 100 µS
B-16A fuse	30 pcs
C-16A fuse	51 pcs
Operating temperature	-25° to +50°C
Rated life (L90B10)	50,000 hours



LED Battens

Futura

Ordering information

Name	SKU	Power	Lumen	Efficacy
Batten-Futura max 2 - 4ft PC 8800Lm - 4000K	18030	52 W	7640 Lm	147 Lm/W