

**Features**

Productgroup	Pyramid ledpanel
Colour	Matte white RAL 9016
Input voltage	110 - 240 Vac on TCI driver
Frequency	50 - 60 Hz
Colour rendering index (CRI)	83
Colour Consistency (SDMC)	MacAdam step 3
Beam angle	85 °
Housing	Diecast Aluminium
Ingress protection	IP20
Impact protection	IK03
IEC safety class	III
Operating temperature	-20°C / +45°C

Benefits

- + Easy installation
- + Innovating reflector technology
- + Low glare in combination with high light output
- + Almost no stray light, "Full width tenth maximum" of 95°
- + Warranty 7 years
- + Perfectly suitable for environments where a true colour is vital
- + Perfect replacement for modular ceiling systems (fluorescent tubes)
- + Ideal application in commercial buildings: schools, universities, hospitals, airports, offices, metro stations and conference rooms
- + No-dim or dimmable (DALI or 0-10V) drivers available
- + Flexible lumen packages selectable by changing driver settings



Compliances

IEC 60598

IEC 62031

IEC 62471

EN 55015

General requirements for luminaires

LED modules for general lighting - Safety specifications

Photobiological safety of lamps and lamp systems

Limits and Methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment