



**Benefits**

- + Perfectly suitable for environments where a true colour is vital (CRI up to 96)
- + White diffuser when light is off
- + Passive heat sink, no moving parts
- + Directional and 359° rotatable
- + Available as spot, medium and flood for the ideal highlight
- + High lumen output versions available on request
- + No-dim or dimmable (DALI / 0-10V) drivers available
- + Flexible Lumen packages selectable by changing driver settings
- + Warranty 5 years

**Features**

Productgroup	Silver Highlite double directional
Colour	Matte white RAL 9016
Input voltage	110 - 240 Vac on TCI driver
Frequency	50 - 60 Hz
Input power	27.9 Watt
Colour Consistency (SDMC)	MacAdam step 3
Housing	Diecast Aluminium
Ingress protection	IP20
Impact protection	Ik03
IEC safety class	2
Power factor	0.95
Inrush current	5 A 50 μS
B-16A fuse	25
Operating temperature	-20 °C to + 45 °C
Rated life (L80B50)	78,000 hours

**Compliances**

IEC 60598

IEC 62031

IEC 62471

EN 55015

General requirements for luminaires

LED modules for general lighting - Safety specifications

Photobiological safety of lamps and lamp systems

Limits and Methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment