LED Interior Illumination
Silver Highlite directional

Benefits

- Perfectly suitable for environments where a true colour is vital (CRI up to 96)
- White diffuser when light is off
- Passive heat sink, no moving parts
- Directional and 359° rotatable
- Available as spot, medium and flood for the ideal highlight
- High lumen output versions availeble on request
- No-dim or dimmable (DALI / 0-10V) drivers available
- Flexible Lumen packages selectable by changing driver settings
- Warranty 5 years

Features

Productgroup	Silver Highlite directional
Colour	Matte white RAL 9016
Input voltage	110 - 240 Vac on TCI driver
Frequency	50 - 60 Hz
Input power	27.9 Watt
Colour Consistency (SDMC)	MacAdam step 3
Housing	Diecast Aluminium
Ingress protection	IP20
Impact protection	IK03
IEC safety class	2
Power factor	0,95
Inrush current	5 A 50 µS
B-16A fuse	50
Operating temperature	-20° to +45°C
Rated life (L80B50)	78,000 hours

IP20

LED Interior Illumination
Silver Highlite directional

Dimensions



Ordering information

Name	SKU	Colour	Beam Angle	Power	Lumen	Efficacy	CCT	CRI
Silver Highlite directional Matte white RAL 9016								
Highlite Silver directional. 3000K. 37°	20049	Matte white RAL 9016	37 °	27 W	3000 lm	111 lm/W	3000 K	82
Highlite Silver directional. 3000K. 60°	20050	Matte white RAL 9016	60 °	27 W	3000 lm	111 lm/W	3000 K	82
Highlite Silver directional. 4000K. 37°	20051	Matte white RAL 9016	37 °	27 W	3400 lm	126 lm/W	4000 K	82
Highlite Silver directional. 4000K. 60°	20052	Matte white RAL 9016	60 °	27 W	3400 lm	126 lm/W	4000 K	82

Compliances

IEC 60598	General requirements for luminaires
IEC 62031	LED modules for general lighting - Safety specifications
IEC 62471	Photobiological safety of lamps and lamp systems
EN 55015	Limits and Methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment

All product, product specifications and data are subject to change without notice to improve reliability, function, design or otherwise. Photos and pictures are for illustration purpose only