

**Features**

Productgroup	Silver ledpanel
Colour	Matte white RAL 9016
Power supply	Need to be ordered separately
Maximum driver current	1050 mA
Input voltage	110 - 240 Vac on TCI driver
Frequency	50 - 60 Hz
Input power	56 Watt
Lumen output	5650 lm
Efficacy	101 lm/W
Colour temperature (CCT)	3000 4000 K
Colour rendering index (CRI)	83
Colour Consistency (SDMC)	MacAdam step 3
Beam angle	85 °
Unified Glare Rating (UGR)	>19
Housing	Steel
Ingress protection	IP20
Impact protection	IK03
IEC safety class	III
Operating temperature	-20° to +45°C
Rated life (L80B50)	>100.000 hours

Ordering information

Name	SKU	Colour	Beam Angle	Power	Lumen	Efficacy	CCT	CRI
Silver LED panel 300x1200 3000K No PSU	18757	Matte white RAL 9016	85 °	56 W	5650 lm	101 lm/W	3000 K	83
Silver LED panel 300x1200 4000K No PSU	18758	Matte white RAL 9016	85 °	56 W	5650 lm	101 lm/W	4000 K	83
Silver LED panel 600x600 3000K No PSU	18755	Matte white RAL 9016	85 °	56 W	5350 lm	96 lm/W	3000 K	83
Silver LED panel 600x600 4000K No PSU	18756	Matte white RAL 9016	85 °	56 W	5650 lm	101 lm/W	4000 K	83