

**Benefits**

- + Perfectly suitable for environments where a true colour is vital (CRI 95)
- + White polycarbonate diffuser when light is off
- + Passive heat sink, no moving parts
- + Fits in standard 185-205 mm apertures
- + Low recess depth of 75 mm
- + Waterproof front
- + Optional DALI, 0-10V or EOS dimmable driver

Features

Productgroup	Silver Shop 185 V2
Colour	Matte white RAL 9016
Power supply	TCl driver included
Input voltage	110 - 240 Vac on TCl driver
Frequency	50 - 60 Hz
Efficacy	110 lm/W
Colour rendering index (CRI)	95
Colour Consistency (SDMC)	MacAdam step 3
Beam angle	80 °
Housing	Diecast Aluminium
Ingress protection	IP20 / IP44
Impact protection	IK03
Operating temperature	-20° to +45°C
Rated life (L80B50)	160,000 hours

Accessoires

14239 Interior. Correction ring - Silver 185 - 290x185

Compliances

IEC 60598

IEC 62031

IEC 62471

EN 55015

General requirements for luminaires

LED modules for general lighting - Safety specifications

Photobiological safety of lamps and lamp systems

Limits and Methods of measurement of radio disturbance characteristics of electrical lighting and similar equipment.